

Modular chimneys

Model	Internal pipe (mm)	Inner diameter (mm)	Outer diameter (mm)	Safety distance (mm)	Heat class	Weight (kg/m)	CE approval	Model
KASTOR KC MODULE CHIMNEY 130	1	130	250	50	T600	approximately 11 kg	Yes	KASTOR KC MODULE CHIMNEY 130
KASTOR KC MODULE CHIMNEY 150	1	150	270	50	T600	approximately 13 kg	Yes	KASTOR KC MODULE CHIMNEY 150

Outer mantle available in colours RST and painted in black.. Internal pipe acid resistant.
Lengths of parts 250 mm, 500 mm and 1,000 mm. Useful lengths 190 mm, 440 mm, 940 mm.

Chimney set

Model	Internal pipe (mm)	Inner diameter (mm)	Outer diameter (mm)	Safety distance (mm)	Heat class	CE approval	Weight (kg/m)
CHIMNEY SET-130	1	130	250	50	T600	Yes	(approximately) 11

Outer mantle RST. Internal pipe acid resistant.

Kastor Chimney Set:
Insulated part 2,000 mm.
Insulated part extendable max. up to 5 metres.

Kastor Chimney Set includes:
Uninsulated connecting pipe, insulated part, rain cap, rain collar, ceiling plate (inclination 0-30°).

Model	Length of straight pipe element [A] (mm)	Lateral movement [B] (mm)	Rise (mm)	Angle of pipe bend
LATERAL MOVEMENT				
2 x pipe bend	–	116	371	30°
2 x pipe bend + straight pipe element 250	250	209	532	30°
2 x pipe bend + straight pipe element 500	500	334	749	30°
2 x pipe bend + straight pipe element 1000	1000	584	1182	30°

Lateral movement with straight pipe element 500 mm

